



## GENSETS

### Power Generation:

- 5000 Watt to 3 Megawatt
- Field Run, Reman, New
- Natural gas, propane, duel fuel or diesel
- Single/Multi-Phase, multiple voltage
- Control Options: Digital, analog, telemetry
- Open or enclosed, shelter or sound attenuation
- Paralleling, synchronization, switch gear, transformers

Model	Kilowatts	Engine	Volts			AMPS		
			1 Phase	3 Phase	3 Phase	1 Phase	3 Phase	3 Phase
GO20KWP	20	GM, Kubota, Doosan	120/240	120/208	277/480	60	60	25
GO40KWP	40	GM, Kubota, Doosan	120/240	120/208	277/480	200	175	80
GO60KWP	60	GM, Kubota, Doosan	N/A	120/208	277/480	N/A	200	90
GO70KWP	70	Cummins 5.9L	N/A	120/208	277/480	N/A	275	125
GO90KWP	90	Cummins 8.3L	N/A	120/208	277/480	N/A	350	150
GO120KW	120	Cummins 8.3L Turbo	N/A	120/208	277/480	N/A	334	145
GO200KW	200	CAT, Cummins, Doosan	N/A	120/208	277/480	N/A	555	240
GO250KW	250	Waukesha, CAT, Cummins	N/A	120/208	277/480	N/A	695	300
GO500KW	500	Waukesha, CAT, Cummins	N/A	120/208	277/480	N/A	1390	600
GO750KW	750	Waukesha, CAT, Cummins	N/A	120/208	277/480	N/A	2085	905



## ENCLOSURES

### Enclosures:

#### Insulated Galvalume (Utilidor)

- 1-1/2" or 2-1/2" foam injected 16 gage Galvalume panels
- Aluminum mounting channels
- Custom Designs

#### Self Framing

- 22 gage galvanized self framing panels
- Custom designs

#### Seacan

- Customized Seacan enclosures to fit your need
- Robust
- Transportable

#### Sound Attenuation available to the above enclosures

- Custom built
- Designed to specified sound levels
- Sound attenuated discharge chambers
- Optional intake air motorized louvers (run/open-off/close)
- Optional access doors for easy service & stub-up area
- Unit painted to customer specifications

For inquiries, please contact (780)871-4800

Box 328 Kitscoty, AB T0B 2P0

[www.gotechnologies.ca](http://www.gotechnologies.ca)